

Hawkhead, Inc 1331 Pickettville Road Jacksonville, FL 32220 Phone- 904-264-4295

PRODUCT DATA SHEET: HWK-2000 Woven

PRODUCT DESCRIPTION:	HWK-2000 is a heavy duty composite woven from yarns containing brass wire. This dense, tough material exhibits exceptional resistence to heat and compression under load. HWK-2000 has excellent fade and recovery stability.					
APPLICATION:	HWK-2000 is suitable for light to heavy duty service with steel and cast iron mating surfaces. It is also suitable for light to medium duty operation in oil. Applications include winches, cranes, hoists, and other heavy duty industrial applications.					
PHYSICAL PROPERTIES:	Width- Up to 20" Thickness125"- 1.250" Length- 25 foot rolls Specific Gravity- 1.6 Tensile Strength- 4200 (ASTM D638)					
FRICTION PROPERTIES: Coefficient of Friction:	Normal @ 400 F.		.53 .53	Hot Static	.53 .56	
Friction Code:	GG					
Recommended Operating Limits:Max. Pressure, psi250Max. Rubbing Speed, ft/min5000Temperature Max. F., intermittent600Temperature Max. F., continuous550						
COEFFICIENT OF FRICTION from SAE J661 test procedure						
Wear Phase			Second Fade			
		- 6.0 -				
5 5 10.4 10.4 10.4 10.3 10.3 10.2 10.2		- 0.4 - 10.4 - 20.3 - 00.2 - 0.2 -				
0.1		0.1 - 20	00 300 Drur	400 500 n Temperatu	600 700 re	